

```

CREATE TABLE xxraj_gl_interface_load_tbl
(
  Batch_Name          VARCHAR2(240),
  Header_Name        VARCHAR2(240),
  JE_Category         VARCHAR2(30),
  JE_Source           VARCHAR2(30),
  Period_Name        VARCHAR2(10),
  Accounting_Date     DATE,
  Concatenated_Segments VARCHAR2(120),
  Segment1           VARCHAR2(30),
  Segment2           VARCHAR2(30),
  Segment3           VARCHAR2(30),
  Segment4           VARCHAR2(30),
  segment5           VARCHAR2(30),
  Segment6           VARCHAR2(30),
  Accounted_DR       NUMBER,
  Accounted_CR       NUMBER,
  Batch_Description  VARCHAR2(240),
  Header_Description VARCHAR2(240),
  Line_Description   VARCHAR2(240),
  Currency_Code      VARCHAR2(3),
  Conversion_Rate    NUMBER,
  Conversion_Type    VARCHAR2(30),
  Actual_Flag        VARCHAR2(1),
  Creation_Date      DATE,
  Line_Number        NUMBER
)
ORGANIZATION EXTERNAL
(TYPE ORACLE_LOADER
(DEFAULT DIRECTORY gl_in_files
ACCESS PARAMETERS
(RECORDS DELIMITED BY NEWLINE
FIELDS
TERMINATED BY '|'
OPTIONALLY ENCLOSED BY '"'
MISSING FIELD VALUES ARE NULL
(
  Batch_Name          ,
  Header_Name        ,
  JE_Category         ,
  JE_Source           ,
  Period_Name        ,
  Accounting_Date     ,
  Concatenated_Segments ,
  Segment1           ,
  Segment2           ,
  Segment3           ,
  Segment4           ,
  Segment5           ,
  Segment6           ,
  Accounted_DR       ,
  Accounted_CR       ,
  Batch_Description  ,
  Header_Description ,
  Line_Description   ,
  Currency_Code      ,
  Conversion_Rate    ,
  Conversion_Type    ,
  Actual_Flag        ,
  Creation_Date      ,
  Line_Number        ,
)
)
LOCATION ('GL_INTERFACE.txt')
);

```